

E³Matrix-C1000-261

Liquid Cooling Energy Storage Cabinet

Three-Phase Four-Wire, 100% Unbalanced
Off-Grid Load and Active Management

Pack-Level Liquid Cooling and Fire Suppression

Max. 3°C Battery Temperature Difference, Higher Consistency



Enhanced Security

- 6 kinds of components monitoring in pack-level fire detection;
- Independent pack-level Perfluorohexanone fire suppression;
- Separated chamber for PCS and battery to isolate interference;
- IP67 for battery pack to prevent arcs and flammable gases, eliminating fire risk.

Easy and Intelligent O&M

- Modular design, quick commissioning and small footprint;
- Intelligent O&M, cloud monitoring of PCS, batteries, failure alarm data analysis, and unattended operation supported;

High efficiency

- 1% efficiency increase with 3P4W+ANPC+hybrid vector modulation algorithm;
- 30% self-consumption reduction with intelligent frequency variable liquid cooling and parallel pipelines for each pack.

Long Service Life

- Max. 3°C temperature difference among battery cells with pack-level independent liquid-cooling, extending service life;
- IP66 for PCS, strengthen protection against harsh environment;
- Wide-range variable speed fan, extending the fan lifespan;
- Intelligent PCS thermal management, reduces devices temperature and enhances reliability.

Technical Parameter

Model	E ³ Matrix-C1000-261
DC parameter	
Type of battery cell	314Ah
Pack capacity/Grouping method	52.25kWh/1P52S
System capacity/Grouping method	261kWh/1P260S
Operating voltage range	728~949Vdc
AC parameter	
Rated power	130kW
Max. continuous power	143kW
Max. power	156kW
Rated voltage	400Vac
Rated current	188A
Rated frequency	50Hz/60Hz
Voltage range	±20%
Frequency range	±5Hz
Current THD	<1.5%@nominal power
DC component	<0.5%In
Power factor	-1~+1 continuously adjustable
Connection method	3P+N+PE
System parameter	
Charge/Discharge rate	≤0.5C
Depth of discharge	100%DOD
Cell cycle life	≥8000
Charge/discharge transfer time	≤30ms
Communication interface	LAN
Relative humidity	<95%(no condensation)
Altitude	4000m(>3000m derating)
Protection degree	IP55(IP67 for PACK and IP66 for PCS)
Noise	≤75dB
Cooling method	Intelligent liquid cooling + air cooling
Fire protection system	Pack-level perfluorohexanone + Early warning Pack-level dual-functional detection(standard) Pack-level hexa-functional detection(optional)
Dimension(W*H*D)	1000mm*1340mm*2300mm
Weight	2500kg
Operation temperature	-25~+60°C(>50°C derating)

XI'AN WEIGUANG ENERGY TECHNOLOGY CO. LTD

Service Number 86-18629469957
global_service@weiguangenergy.com